



CE II 2GD
Ex h IIC T6 Gb
Ex h IIIC T85°C Db




Für die sichere Rückgewinnung von brennbaren / leitfähigen
Stäuben GARANTIE

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Charakteristik



EX Certified




Less than 10 ohms



Dry Recovery



Wet and Dry Recovery



ULPA - Included



High Filtration Efficiency Unit



SS 304 and 316



SD Accessories - Included



- Statisch ableitend und leitfähig
- Weniger als 10 ohm des Widerstands
- ULPA filter - downstream - included. With an efficiency of 99.9995% at 0.12 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822 and OSHA compliant. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility. HEPA filter - upstream - also included for dry only version
- Reinraum mit ISO Klasse 4 (fr?here Klasse 10) kompatibel. Kann in der Pharmaindustrie verwendet werden
- For dry recovery only or wet & dry recovery
- All stainless steel Type 304/316 construction
- Ein komplettes statisches ableitendes ToolKit ist enthalten.
- Niedriges Geräuschniveau - nur 68 dB(A)
- The recovery tank is made of stainless steel Type 316 and is fully autoclavable (up to 121°C) including the white nylon wheels. Static conductive grey wheels (non-autoclavable) are available upon request
- Pressure regulator included. Pressure regulator is adjustable between 0 psi. (0 bar) to 150 psi. (10 bars). It is factory set at 80 psi. (5.5 bars) for ideal performance and noise level

Specifications

ATEX-40A (CR)	111803-CR	111803-CRWD
Model Name	ATEX-40A (CR)	ATEX-40A (CR) WET & DRY
Typ (Motor)	Pneumatic	Pneumatic
Venturi	Single	Single
Kompressor	15 HP	15 HP
Airline Größe	1/2" (12.7mm)	1/2" (12.7mm)
Eingang Luftvolumen	16.5-21.2 L/s	16.5-21.2 L/s
Eingang Luftdruck	5.5 Bar	5.5 Bar
Luftstrom	187 m ³ /h	187 m ³ /h
Saugdruck	2790 mm H ₂ O	2790 mm H ₂ O
Geräuschpegel	68 dB(A)	68 dB(A)
Ansaugeinlass	38 mm	38 mm
Fahrgestelltyp	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Länge	48 cm	48 cm
Breite	46 cm	46 cm
Höhe	86 cm	86 cm

Bitte beachten Sie, dass die Spezifikationen ohne vorherige Ankündigung geändert werden können



Disposable Conductive Filter Bag - Included



Conductive Main Cloth filter and Cage - Included



Stainless Steel Floater (Liquid Cut-Off) for Wet & Dry Version - Included



Air Supply Hose Assembly, Static Dissipative and Conductive - Included



#323604 - Ø1.25" (Ø32 mm) Autoclavable tools and accessories (Kit #3) - Included