


Clean-Room ESD Professional C-EX1663HAS / C-EX1673HAS

PRODUCT	DIMENSIONS	A-EX1663HAS	A-EX1673HAS
	Seat depth from lumbar support	440 mm	440 mm
	Seat depth	470 mm	470 mm
	Seat width	510 mm	510 mm
	Backrest height from seat	530-590 mm	530-590 mm
	Backrest height adjustment	60 mm	60 mm
	Backrest width	470 mm	470 mm
	Seat height	500-700 mm	600-850 mm

TECHNICAL DESCRIPTION	
Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection. Additional shell in recyclable techno-polymer for mechanism total encasement and protection.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in antistatic ESD recyclable techno-polymer for internal components protection.
Padding	Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	ECR7 Composition: 90% PVC, 10% cotton/polyester Weight: 880 g/lmt Resistant to disinfectants Colors: Black 1104
Mechanism	ASX : A-SYNCHRON X. Combined tilting of seat and backrest of 6°. Additional independent backrest inclination of 25° for a total backrest inclination 31°. Both adjustments are lockable in all position. With antishock. Up&Down activated backrest height adjustment, lockable in 7 positions. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	0903C : 5-star base (∅ 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0331 : Conductive glides in black nylon (h 32 mm / ∅ 50 mm).

ACCESSORIES	
M-0321	Conductive castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of castors.
0860AN	Height adjustable conductive armrests. Supporting structure in steel with top in conductive nylon. Black finish.
0830N	Height adjustable armrests. Supporting structure in reinforced nylon, shock-resistant and scratch-resistant, with top in soft polyurethane. Black finish.
0700ESD	Conductive circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
NO-OIL	Gas lift with sealing ring for oil and grease.

TEST
UNI EN 1335-1+2+3
EN 100015-1
IEC 61340-5-1