


Clean-Room HEPA C-VV112S

PRODUCT	DIMENSIONS	C-VV112S	
	Seat depth from lumbar support	440 mm	
	Seat depth	440 mm	
	Seat width	460 mm	
	Backrest height from seat	510-580 mm	
	Backrest height adjustment	70 mm	
	Backrest width	470 mm	
	Seat height	440-570 mm	

TECHNICAL DESCRIPTION	
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. Hermetic PVC profile seal. HEPA 200 P2P EN 143:00 filter for dust particles.
Backrest	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. Hermetic PVC profile seal.
Padding	Seat in PU-Flex, 45 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.
Upholstery	<p>VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colors: Throna color chart</p> <p>TOLEDO Composition: 84% PVC, 16% polyester Weight: 1.036 g/lmt Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Resistant to disinfectants, blood and urine. Colors: Black 014</p>
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment (70 mm). According to UNI EN 1335-3.
Lift action	NO-OIL: Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish, with sealing ring for oil and grease retention. Class 4 according to DIN 4550.
Base	0907C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	0311: Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.

Clean-Room HEPA C-VV1112S

ACCESSORIES

M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
--------	--

TEST

UNI EN 1335-1+2
D. Lgs. 81/2008 type B
UNI EN1022:2018
UNI EN 1728:2012+AC:2013